

Continuon™ 8U/CHS

Netra™ Blade Compute Farm Platform



Ordering Information

Continuon™ 8U/CHS

Standard Configuration includes :

- C0818D 8U System Platform
- Two CP1500 or two CP20xx SBC & Rear I/O
- SPARC Processors
- Two PICMG 2.16 Switch Fabric boards
- 256MB ECC SDRAM
- Additional CPxxxx Computing Blades

Power Subsystem Options

PSU-AC

Four 200W N+1 AC power supplies

PSU-DC

Four 200W N+1 -48VDC power supplies

PIM-AC

Redundant AC isolated input modules

PIM-DC

Redundant DC isolated input modules

PIM-UPS

AC input module and an embedded UPS kit

Control & Monitoring Options

IBC-2501

Chassis Management Controller, IPMI v.1.0 compliant Module.

Memory & Drive Options

From 18 GB to 36GB SCA drives

Specifications

Chassis

8U Height

- 14" x 17.1" x 12" (hwd) 356 x 434 x 304 mm

Up to sixteen IBC 280x server blades

Sun Netra™ CP 2060 SBC

- 500MHz Ultra SPARC™ IIe 64-bit processor
- Solaris 8 CD 6 Operating System
- Integrated 4-way 256KB L2 cache
- 512MB soldered on board ECC RAM
- 1MB on-board boot flash, 4MB user programmable flash memory
- Sun Microcontroller, IPMI interface
- One PMC 32 bit 33MHz available
- Two RS-232C asynchronous serial ports
- Two USB ports
- Two 10/100 Mb/sec. Ethernet Interfaces
- Ultra-2 SCSI PMC with Rear I/O
- 1-Slot (4HP) x 6U **CompactPCI®** Compliant
- **CompactPCI®** Compliant Rear I/O Board

Supported SBCs

CP2040, CP2060, CP2080, CP1500

Two PICMG 2.16 Compliant Fabric Switch Boards

- Carrier-grade 24 port 10/100 + 2 ports Gb switches
- Wire-speed layer 2/layer 3 (IP) switching

Backplane

- Integrated 8 + 8-slot CPCI segmented backplane
- System slots #1 and #9
- 14 full hot-swap I/O slots
- 7 + 7-slot segmented H.110 backplane
- Fully PICMG 2.16 PSB Compliant

Fail-Safe OPTICOOL™ Cooling

- Patented push-mix-pull cooling technology
- 8 + 2 fan, hot-swap cooling array in air intake
- Patented air flow mixing and directing tray
- 3 individually hot-swap blowers
- Optional blower and fan speed control with I-Bus CMC

DC Power Subsystem

- 4 Hot-swap redundant -48VDC power supplies
- N+1 Redundant (N=3) 200W supplies
- Dual feed power inputs
- Input Voltage: -36 to 72 VDC auto-ranging
- Output Power: +3.3V@30A, +5V@25A, +12V@5.5A, -12V@0.5A (each supply)
- Combined power of +5 and +3.3V not to exceed 35A total per supply

Operating Environment

- Temperature: 0 to 40° C
- Humidity: 5% to 85% @40° C, (non-condensing)
- Shock: 10g @11mS
- Vibration: 0.25G @2-100Hz, 1.5g@100-500Hz

Standards Compliance

- PICMG 2.0 R 3.0, PICMG 2.1 R 2.0, PICMG 2.5 R 1.0, PICMG 2.9 R1.0, PICMG 2.10 R 1.0, PICMG 2.11 R 1.0, PICMG 2.16 R 1.0
- ESD: CE
- EMI: CE, FCC, UL/CUL
- Safety: UL/CUL, CE, CB
- NEBS



Continuon™ 8U/CHS


Netra™ Blade Compute Farm Platform

The state-of-the-art **Continuon™ 8U/CHS** CompactPCI PSB platform is the highest density Backplane solution on the market today, and the first to employ I-Bus patented Fail-Safe OptiCool™ technology. In 8U of space all critical modules are easily accessible and fully hot-swap capable. It supports full I/O card hot-swap to PICMG 2.1 R2.0, dual hot-swap power input modules and N+1 redundant hot-swap power supplies.

In 8U the most critical component is the cooling. I-Bus continues to lead the CompactPCI market with the patented Fail-Safe OptiCool™ method of push-mix-pull cooling. Fail-Safe Opticool incorporates a unique lower hot-swap fan array that takes advantage of the axial direction of the fans to most efficiently pressurize the air at the bottom of the chassis. The unique mixing tray can be tuned to mix the intake air, redirect the air upward and distribute the air to where it is needed most, even in the event of a single fan failure. To direct the air through the cards, drives and power supplies, three individually hot-swappable blowers pull the low pressure air upward and direct it toward the rear of the chassis. Optimization of cooling, noise and blower life expectancy is achieved with the addition of the optional I-Bus Chassis Management Controller (CMC), which provides independent speed control for the individual blowers and the fan array. The CMC is added in its dedicated slot at the rear of the chassis.

With all of these high-availability features, the **Continuon™ 8U/CHS** excels in applications requiring small size, optimal cooling, high density and the highest levels of reliability, serviceability and maintainability, ensuring the greatest level of application availability. Additional features include a 16 + 2 slot CPCI/H.110 backplane, full rear I/O module support, front to back airflow and NEBS compliance.

The Continuon™ 8U/CHS is the Best of Class solution on the market achieving high system availability.



[For Further Information](#)



Worldwide Headquarters

I-Bus Corporation
 3350 Scott Blvd, Building 54
 Santa Clara, CA 95054
 United States
 Phone : +1 (408) 450-7880
 Fax : +1 (408) 450-7881
Toll Free: 877-777-IBUS
 Email: contact.us@ibus.com

European Headquarters

I-Bus UK Ltd
 Unit 6, Chichester Business Park
 City Fields Way, Tangmere
 West Sussex, PO20 2LB, UK
 Tel: +44 (0) 1243 756300
 Fax: +44 (0) 1243 756301
 Email: contact.uk@ibus.com

France, Italy

I-Bus France
 B.P 45 Valbonne
 06901 Sophia Antipolis CEDEX
 France
 Tel: +33 (0) 493 004 360
 Fax: +33 (0) 493 004 369
 Email: contact.fr@ibus.com