

# TR2

## 2U ISA & PCI Rackmount Enclosure



### Ordering Information

#### DESKTOP or RACKMOUNT

##### TR2-19-BLK-005

2U rackmount enclosure, w/5-slot ISA backplane & 400W AC power supply

##### TR2-19-ISA/PCI-BLK-006

2U rackmount enclosure, w/6slot ISA/PCI backplane & 400W AC power supply

#### Rack Slide Options

##### SL2-20

20" rack slides, ball bearing

##### SL2-24

24" rack slides, ball bearing



Left hand view:  
Passive backplane ISA



Right hand view:  
Passive backplane ISA

### Specifications

#### Dimensions

- 2U height
- 3.5"H x 17"W x 16" or 19"D  
89mm(H) x 432mm(W) x 406mm(D)  
or 482mm(D)

#### Standard Colour Options

- Black, Cream and Grey

#### Backplanes

- 5-Slot ISA
- 6-Slot ISA /PCI

#### Fan MTBF

- 70,000 hrs. @ 40° C

#### Drive Bays

- Locking drive door
- Shock mounted drive bay
- One 5.25" & two 3.5" drives

#### Rear Panel

- AC inputs for power supplies

#### Cooling

- Two 49.4CFM fans
- Front accessible & removable fans
- Removable front filter

#### Front Panel Options

- Access to drives
- Two LEDs, one green "power" & one red "hard drive activity"

#### Power Supplies

##### PSU2395

- Single 400W PSU(AC, 90-132/180-264Vac)  
(+5V@ 50A) (+12V@ 27A)  
(-5V@ 1A) (-12V@ 3A)

##### PSU2396

- Single 400W PSU(AC, 90-132/180-264Vac)  
(+5V@ 50A) (+12V@ 27A)  
(-5V@ 1A) (-12V@ 3A) (+3.3V@ 30A)

#### Power Supply MTBF

- 80,000 hrs.

#### Operating Environment

- Temperature: 0 to 50° C
- Humidity: 5% to 95% @ 45° C, (non-condensing)

#### CE Approval

- EN 55022 Class A
- EN 50082-1
- EN 60950

